



SEGATRONCHI

TECNOUTENSILI S.R.L.

Via IX strada n°03 - 95020 Catania - Italia

+39 095 712.53.23

www.segatronchi.it / segatronchi@gmail.com

CTR 710



4820 x 35 x 0,9 -1,1 mm




Feed into the cut and back – motor-powered**Arm height adjustment – motor-powered**

Max. log diameter	710 mm
Max. opening between blade guides	660 mm
Max. elevation of blade	630 mm
Min. log height	30 mm
Max. depth of cut	450 mm
Max. log length (standard model)	2,1 m
Length track section	1 m / 3 m

Control panel – on a mobile bridge**Log handling – manual**

Min. log length	1 m
Saw blade motor	5,5 (7,5) kW
Horizontal feed motor	0,37 kW
Vertical feed motor	0,55 kW
Sawblade	4140 × 35 – 40 × 0,9 – 1,1 mm
Weight (standard model)	680 kg
Weight (track section)	25 kg / 97 kg

Smaller, but truly professional saw band in all respects. Execution of main technical parts, such as the running wheels in their mounts, construction of the saw band arm, engine and feeding systems, etc., are completely identical to those in CTR 800 series or in very powerful CTR 950 Hydraulik and CTR 1000 H/40. Simple hand feed into the cut and back. Motor-powered saw band arm height adjustment. In this version of the machine the control panel is placed on a mobile bridge of the saw band arm. Thanks to that the operator has closer access to the workpiece when cutting.




The feed into the cut and back is driven by an electric motor with worm gearbox controlled by a frequency converter. You can change the speed of travel simply by turning the potentiometer on the control panel. End positions are secured against impact by means of limit switches with automatic deceleration and stopping.

The massive saw band arm is borne on adjustable hard-chromium rods (for moving up and down) which ensure absolute accuracy of saw band arm movement and virtually unlimited service life, if the machine is lubricated regularly. The vertical movement of the arm is provided by double-sided synchronous chain transmission powered by an electric motor with worm gearbox. The movement controlled from the central panel has two modes of speed – rapid feed and slow feed for accurate movement to a desired position. This system can be always additionally equipped with electronic metering which automatically moves to the specified position.


The arm is fitted with running wheels made of high-quality grey cast iron with accurate balancing against vibrations. The wheel has a groove along its circumference. The groove holds a replaceable rubber-textile belt which creates an optimum contact area between the wheel and the saw band.

The sturdily mounted running wheel is powered through a wedge belt by a professional electrical motor specially balanced against vibrations.

The tensioning wheel system moves along a sturdy cast iron wedge guide with adjustable pressure bar, which allows highly accurate adjustment without any free travel even in long-term machine operation.



The saw band is guided in the cut by hardened and ground guide pulleys. This system can be fully adjusted in all directions and it ensures optimum position of guide pulleys and the saw band.



In order to ensure accuracy of the cut the guide pulley on the operator's side moves as close as possible to the workpiece. Simply operated massive bearing system. It can be motor-powered and controlled as an auxiliary device from the control panel.



Stable running sections with steel arm bridge guides form the basis of the machine. They are sufficiently dimensioned for maximum diameters of logs as well. They were designed reflecting the practice, therefore designed to cope with very hard operating conditions. Cut length is virtually unlimited in all types of machines, it only depends on the length of running gear installed. Running gear sections are fitted with massive, height-adjustable log-bearing surfaces and adjustable retractable angles and log clamps. The basic version of the machine includes 3 workpiece clamps and 2 angular steady bars.



Gravity cooling and lubricating of the band with adjustable outlets in both guide pulleys ensure that the saw band is in optimum condition during cutting.

CTR series present the latest trends in construction of log saw bands with a special emphasis on maximum accuracy and long-term service life of the machine while ensuring minimum costs. The machines are designed in an original modular execution which allows easy replacement or adjustment of all main technical sections and their individual parts. This in the long-term perspective reduces the maintenance costs, service times and therefore production stoppages as well.

Accessories – There is a wide range of accessories to all of these machines. They simplify and accelerate machine operation and influence its production. Our original modular system allows additional installation of necessary equipment at any time, because all basic versions of machines include all fitting spots including holes and threads.

SPECIAL ACCESSORIES




Track section

1 meter – basic rails only
3 meter – contain in basic: 3x cross beams, 2x angle arms.
Another variable points: 3x material clamps.



Lever

For handling, loading and turning the log on the machine frame.



Main motor 7,5 kW

Stronger output of motor provides faster cut, mainly with huge diameters of logs



LG 100

It is intended for a quick and accurate setting of required board thickness. The movement of the band saw arm up and down is displayed with an accuracy of 0.1 mm on a colour display. The absolute height from the band saw bed or, after reset, the set board thickness including the optional kerf thickness is displayed.



LG automat

Digital measuring system for fast and accurate automatic setting of the desired thickness of the cut.
After the specification of basic settings (height from the loading area and cut-through) and of the desired value (cut thickness), the arm with a saw band will automatically move to the required position. That prevents human-induced failures that can arise during manual cut settings. Saves time, refines production.




Pre-cutter

The pre-cutter circular with hard metal tips is designed to remove dirt at points where the saw blade cuts into the log. The saw blade do not get blunt quickly. Frequent saw blade exchanges are reduced, the saw blade life, and the productivity of the machine increase



Hydraulic saw blade straining

Operated by a hydraulic hand pump with accurate pressure indication. The saw blade straining is more accurate and convenient.



Hard-metal Saw Band Guidance

It is located on the moving rail before the cut. It significantly improves saw band stability in the cut and also in its cleaning. Therefore it increases the machine productivity and cutting accuracy. This machine can be installed on an electrically controlled rail.



Route for feeding logs

Provides easy and safe manipulation on machine cross beams with system of flexible stops.



Pressure two-sided saw band cooling

The cooling system consists of a pressure pump in the coolant tank, flow control solenoid valve and two-way jets that spray the saw band both from below and from above. Two-side cooling prevents undesirable stress in the saw band and adhesion of resin from underneath the saw band and thus helps maintain stabler saw band operation, more accurate cut and longer service life.



Material Clamp

Consists of a rail and a front and rear clamp.



Hand Operated Grease Gun

For regular maintenance of the machine according to the lubrication plan. Metal grease gun for 400g cartridges. Equipped with a flexible pressure tube.



Saw band cooling control

Integrated in the cooling system is an electromagnetic through-flow valve, which automatically opens when the saw blade is started and closes when the saw blade is stopped. It substantially lowers the coolant consumption and saves time needed for replenishment of coolant liquid.



LED lighting (11 W)

Good quality lightening of the workspace using two powerful LED strips mounted on a movable bridge.



ARCTIC version

Version of the machine adapted for work in extremely cold operating temperatures reaching down to -40°C . Machine's switch board, control panel and digital measuring (LG 100, LG Automat) are fitted with heating elements. The heating is controlled through a thermostat. Frost-resistant lubricant. Band saws CTR 800 H, 950 H, 1000 H and 1300 H use frost-resistant hydraulic oil.



Grasso LV 2-3

Cartuccia da 400g, per la pistola per grasso

CONSUMABLE PARTS



Saw Band Guide Pulley VK 35

Hardened ground pulley, bearings, shaft for a saw band 35 mm wide.



Saw Band Guide Pulley VK 40

Hardened ground pulley, bearings, shaft for a saw band 40 mm wide.



Flat Running Wheel Belt GPK 1550

SAW BAND SHARPENERS



Affuteuse semi-automatique OR 50

Une finition extraordinairement étudiée et professionnelle de l'affûteur garantit un affûtage précis de la lame de scie - la condition de base pour une coupe productive et de qualité sur n'importe quelle scie à ruban.

La meule en pierre est une meule fine qui trace la forme de la dent au moyen d'un système de came réglable. Ce système permet le réglage de n'importe quelle forme et taille de dent.

Accessoires:

- base
- lampe halogène
- système de refroidissement



Affuteuse semi-automatique OR 50 F

Cette affûteuse de lame de scie est équipée d'un changeur de fréquence, qui permet une vitesse variable en continu de l'alimentation de la lame de scie. De cette manière, la qualité d'affûtage et la productivité sont accrues.

Une meule en pierre mince trace la forme de la dent au moyen d'un système de came réglable. Ce système permet le réglage de n'importe quelle forme et taille de dent.

Accessoires:

- base
- lampe halogène
- système de refroidissement




Affuteuse semi-automatique OR 71 F

La nouvelle génération d'aiguiser de lame de scie OR 71 F permet d'aiguiser les lames jusqu'à 70 mm. Système entièrement nouveau de réglage de la forme des dents. L'affûteur a son propre système de refroidissement intégré, lampe et convertisseur de fréquence pour permettre un réglage continu de la vitesse d'avance de la lame de scie.

Accessoires:

- base
- meule en pierre (trace la forme de la dent au moyen d'un système de came réglable et permet le réglage de la forme et de la taille de la dent).
- pâte de diamant (appliquée sur la meule en pierre, améliore la rugosité et prolonge la durée de vie de la meule).



RW 71

Un design robuste en fonte assure une longue durée de vie de la machine et une précision de réglage maximale. Deux dents (droite, gauche) ou trois dents (droite, gauche, droite) sont réglées en même temps avec un seul mouvement de levier. Prix incluant un indicateur de réglage de la scie. Bande de scie de 15 à 70 mm de largeur.



SK 35

Ils sont conçus pour ajuster le réglage des dents individuelles.

SAWBLADES

MAXWOOD STELIT

High-quality band saw is the second most important factor (just after the machine construction) for cutting speed and accuracy and maintenance of long service life. Choose your saw band from a wide selection of excellent professional saw bands. CTR 710 uses the saw band sized 4140 mm. The band is manufactured in following versions



Saw blade dimension (mm)		Tooth pitch (mm)		Tooth shape	Tooth face angle
width	thickness	22	25		
35	0,9 / 1 / 1,1	•	•	WM	Standardly 10°. Another face angle on request.
38	1 / 1,1	•	•	WM	
40	0,9 / 1 / 1,1	•	•	WM	




Stellite application is the latest trend in the treatment of cutting edges on saw bands. Stellite is a cobalt-chromium based alloy containing other elements. It is weld directly on the carrier belt in the place of a tooth tip and it forms a compact saw band cutting edge. In contrast to frequently used high-speed steel it is much more resistant to blunting and therefore it doesn't require frequent replacement and sharpening. The band is supplied sharp.

Use of stellite saw bands brings a number of benefits:

- can be used for cutting for up to two shifts without changing or sharpening
- stellite cutting edge is 2 mm wide which eliminates the need for setting of teeth
- allows higher rate of feed into cut
- very fine roughness of the cut surface
- possibility of cutting tropical wood of the highest hardness

MAXWOOD BIMETALIC




Construction of the saw band with a tooth tip made of tool steel which is typically used for cutting iron. The new technology allows significantly longer cutting time without the need for replacement or sharpening of the saw band.

The carrier saw band is made of spring steel alloyed with chromium and the tooth tip is made of HSS material with cutting edge hardness of 67 HRC. The band is supplied sharp, set and polished.

Saw blade dim. (mm)		Tooth pitch (mm)				Tooth shape	Tooth face angle
width	thickness	8,3	12,8	20,3	22		
34	0,9 / 1,1				•	WM	10°
34	1,1	•	•	•		H	10°
41	1,1				•	WM	10°



MAXWOOD




Saw blade dimension (mm)		Tooth pitch (mm)			Tooth shape	Tooth face angle
width	thickness	19	22	25		
35	0,9 / 1 / 1,1	•	•	•	WM	9°/10°/12°
38	1 / 1,1	•	•	•	WM	10°
40	0,9 / 1 / 1,1	•	•	•	WM	9°/10°/12°



Excellent saw band made of C75 alloy steel, manufactured specially for Pilous on the basis of our long-term experience. High teeth setting and geometry accuracy. Excellent combination of high durability and fatigue strength. The band is supplied sharp, set and polished. Unique process of induction hardening of the tooth tip ensures extraordinary service life of the cutting edge. Tooth cutting edge hardness from 43 up to 46 HRC.

MUNKFORS



Saw blade dimension (mm)		Tooth pitch (mm)			Tooth shape	Tooth face angle
width	thickness	19	22	25		
35	0,9 / 1	•	•	•	WM	10°
38	1,1 / 1,25		•	•	WM	10°
40	0,9 / 1		•	•	WM	10°



The Swedish company Munkfors is a leading company in the development of saw bands for woodworking industry. The manufacture process utilizes a unique, patented method of tooth shape cutting. Thanks to this technology the cutting edge is sharper, the band has exceptionally long service life and the cut is smoother. Carrier steel strip UDDEHOLM ensures excellent flex life and durability of the saw band. The saw band is sharp and set, the tooth tips are hardened.

MAXWOOD-S



Saw blade dimension (mm)		Tooth pitch (mm)			Tooth shape	Tooth face angle
width	thickness	19	22	25		
35	0,9 / 1 / 1,1	•	•	•	WM	10°
38	1 / 1,1	•	•	•	WM	10°
40	0,9 / 1 / 1,1	•	•	•		10°



Excellent, durable carrier C75 alloy steel with the addition of nickel achieves hardness of 41–43 HRC and tooth tips are therefore not further heat-treated. The band is characterized by high flex life. The teeth of the saw band aren't set or sharpened